

## 1.1 V to 5.5 V, Slew Rate Controlled Load Switch in TSOT23-6

### DESCRIPTION

The SiP32508 and SiP32509 are a slew rate controlled load switches designed for 1.1 V to 5.5 V operation.

The switch element is of n-channel device that provides low  $R_{on}$  of 44 m $\Omega$  typically over a wide range of input.

The devices guarantee low switch on-resistance at 1.2 V input. They feature a controlled soft-on slew rate of typical 2.5 ms that limits the inrush current for designs of heavy capacitive load and minimizes the resulting voltage droop at the power rails.

These devices feature a low voltage control logic interface (on/off interface) that can interface with low voltage control signals without extra level shifting circuit.

SiP32508 and SiP32509 have exceptionally low shutdown current and provides reverse blocking to prevent high current flowing into the power source.

SiP32509 integrates a switch off output discharge circuit.

Both SiP32508 and SiP32509 are available in TSOT23-6 package.

### FEATURES

- 1.1 V to 5.5 V operation voltage range
- Flat low  $R_{on}$  down to 1.2 V
- 44 m $\Omega$  typical from 1.5 V to 5 V
- Slew rate controlled turn-on: 2.5 ms at 3.6 V
- Low quiescent current < 1  $\mu$ A when disabled  
10.5  $\mu$ A typical at  $V_{IN} = 1.2$  V
- Reverse current blocking when switch is off, with guaranteed less than 2  $\mu$ A leakage
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



### APPLICATIONS

- PDAs / smart phones
- Ultrabook and notebook computer
- Tablet devices
- Portable media players
- Digital camera
- GPS navigation devices
- Data storage devices
- Optical, industrial, medical, and healthcare devices
- Peripherals
- Office automation
- Networking

### TYPICAL APPLICATION CIRCUIT




Fig. 1 - SiP32508, SiP32509 Typical Application Circuit

### ORDERING INFORMATION

| TEMPERATURE RANGE | PACKAGE  | MARKING | PART NUMBER       |
|-------------------|----------|---------|-------------------|
| -40 °C to +85 °C  | TSOT23-6 | LD      | SiP32508DT-T1-GE3 |
|                   |          | LE      | SiP32509DT-T1-GE3 |

#### Note

- -GE3 denotes halogen-free and RoHS-compliant

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER                                                                     | LIMIT       | UNIT |
|-------------------------------------------------------------------------------|-------------|------|
| Supply input voltage ( $V_{IN}$ )                                             | -0.3 to 6   | V    |
| Enable input voltage ( $V_{EN}$ )                                             | -0.3 to 6   |      |
| Output voltage ( $V_{OUT}$ )                                                  | -0.3 to 6   |      |
| Maximum continuous switch current ( $I_{max}$ ) <sup>c</sup>                  | 3           | A    |
| Maximum repetitive pulsed current (1 ms, 10 % duty cycle) <sup>c</sup>        | 6           |      |
| Maximum non-repetitive pulsed current (100 $\mu$ s, EN = active) <sup>c</sup> | 12          |      |
| ESD rating (HBM)                                                              | > 8         | kV   |
| Junction temperature ( $T_J$ )                                                | -40 to +150 | °C   |
| Thermal resistance ( $\theta_{JA}$ ) <sup>a</sup>                             | 150         | °C/W |
| Power dissipation ( $P_D$ ) <sup>a, b</sup>                                   | 833         | mW   |

**Notes**

- a. Device mounted with all leads soldered or welded to PC board, see PCB layout  
b. Derate 6.66 mW/°C above  $T_A = 25$  °C, see PCB layout  
c.  $T_A = 25$  °C, see PCB layout

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating/conditions for extended periods may affect device reliability.

**RECOMMENDED OPERATING RANGE**

| PARAMETER                                      | LIMIT       | UNIT |
|------------------------------------------------|-------------|------|
| Input voltage range ( $V_{IN}$ )               | 1.1 to 5.5  | V    |
| Operating junction temperature range ( $T_J$ ) | -40 to +125 | °C   |


**SPECIFICATIONS**

| PARAMETER                       | SYMBOL        | TEST CONDITIONS UNLESS SPECIFIED<br>$V_{IN} = 5$ V, $T_A = -40$ °C to +85 °C<br>(typical values are at $T_A = 25$ °C) | LIMITS<br>-40 °C to +85 °C |                   |                   | UNIT       |
|---------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------|-------------------|-------------------|------------|
|                                 |               |                                                                                                                       | MIN. <sup>a</sup>          | TYP. <sup>b</sup> | MAX. <sup>a</sup> |            |
| Operating voltage <sup>c</sup>  | $V_{IN}$      |                                                                                                                       | 1.1                        | -                 | 5.5               | V          |
| Quiescent current               | $I_Q$         | $V_{IN} = 1.2$ V, EN = active                                                                                         | -                          | 10.5              | 17                | $\mu$ A    |
|                                 |               | $V_{IN} = 1.8$ V, EN = active                                                                                         | -                          | 21                | 30                |            |
|                                 |               | $V_{IN} = 2.5$ V, EN = active                                                                                         | -                          | 34                | 50                |            |
|                                 |               | $V_{IN} = 3.6$ V, EN = active                                                                                         | -                          | 54                | 90                |            |
|                                 |               | $V_{IN} = 4.3$ V, EN = active                                                                                         | -                          | 68                | 110               |            |
|                                 |               | $V_{IN} = 5$ V, EN = active                                                                                           | -                          | 105               | 180               |            |
| Off supply current              | $I_{Q(off)}$  | EN = inactive, OUT = open                                                                                             | -                          | -                 | 1                 |            |
| Off switch current              | $I_{DS(off)}$ | EN = inactive, OUT = GND                                                                                              | -                          | -                 | 1                 |            |
| Reverse blocking current        | $I_{RB}$      | $V_{OUT} = 5$ V, $V_{IN} = 0$ V, $V_{EN}$ = inactive                                                                  | -                          | -                 | 10                |            |
| On-resistance                   | $R_{DS(on)}$  | $V_{IN} = 1.2$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                       | -                          | 47                | 54                | m $\Omega$ |
|                                 |               | $V_{IN} = 1.8$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                       | -                          | 44                | 52                |            |
|                                 |               | $V_{IN} = 2.5$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                       | -                          | 44                | 52                |            |
|                                 |               | $V_{IN} = 3.6$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                       | -                          | 44                | 52                |            |
|                                 |               | $V_{IN} = 4.3$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                       | -                          | 44                | 52                |            |
|                                 |               | $V_{IN} = 5$ V, $I_L = 100$ mA, $T_A = 25$ °C                                                                         | -                          | 46                | 52                |            |
| On-resistance temp. coefficient | $TC_{RDS}$    |                                                                                                                       | -                          | 3570              | -                 | ppm/°C     |

| SPECIFICATIONS                     |              |                                                                                                                                                                                                 |                                                            |                   |                   |               |
|------------------------------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|-------------------|-------------------|---------------|
| PARAMETER                          | SYMBOL       | TEST CONDITIONS UNLESS SPECIFIED<br>$V_{IN} = 5\text{ V}$ , $T_A = -40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$<br>(typical values are at $T_A = 25\text{ }^{\circ}\text{C}$ ) | LIMITS<br>-40 $^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$ |                   |                   | UNIT          |
|                                    |              |                                                                                                                                                                                                 | MIN. <sup>a</sup>                                          | TYP. <sup>b</sup> | MAX. <sup>a</sup> |               |
| EN input low voltage <sup>c</sup>  | $V_{IL}$     | $V_{IN} = 1.2\text{ V}$                                                                                                                                                                         | -                                                          | -                 | 0.3               | V             |
|                                    |              | $V_{IN} = 1.8\text{ V}$                                                                                                                                                                         | -                                                          | -                 | 0.4 <sup>d</sup>  |               |
|                                    |              | $V_{IN} = 2.5\text{ V}$                                                                                                                                                                         | -                                                          | -                 | 0.5 <sup>d</sup>  |               |
|                                    |              | $V_{IN} = 3.6\text{ V}$                                                                                                                                                                         | -                                                          | -                 | 0.6 <sup>d</sup>  |               |
|                                    |              | $V_{IN} = 4.3\text{ V}$                                                                                                                                                                         | -                                                          | -                 | 0.7 <sup>d</sup>  |               |
|                                    |              | $V_{IN} = 5\text{ V}$                                                                                                                                                                           | -                                                          | -                 | 0.8 <sup>d</sup>  |               |
| EN input high voltage <sup>c</sup> | $V_{IH}$     | $V_{IN} = 1.2\text{ V}$                                                                                                                                                                         | 0.9 <sup>d</sup>                                           | -                 | -                 | V             |
|                                    |              | $V_{IN} = 1.8\text{ V}$                                                                                                                                                                         | 1.2 <sup>d</sup>                                           | -                 | -                 |               |
|                                    |              | $V_{IN} = 2.5\text{ V}$                                                                                                                                                                         | 1.4 <sup>d</sup>                                           | -                 | -                 |               |
|                                    |              | $V_{IN} = 3.6\text{ V}$                                                                                                                                                                         | 1.6 <sup>d</sup>                                           | -                 | -                 |               |
|                                    |              | $V_{IN} = 4.3\text{ V}$                                                                                                                                                                         | 1.7 <sup>d</sup>                                           | -                 | -                 |               |
|                                    |              | $V_{IN} = 5\text{ V}$                                                                                                                                                                           | 1.8                                                        | -                 | -                 |               |
| EN input leakage                   | $I_{SINK}$   | $V_{EN} = 5.5\text{ V}$                                                                                                                                                                         | -1                                                         | -                 | 1                 | $\mu\text{A}$ |
| Output pulldown resistance         | $R_{PD}$     | EN = inactive, $T_A = 25\text{ }^{\circ}\text{C}$ , (for SiP32509 only)                                                                                                                         | -                                                          | 217               | 280               | $\Omega$      |
| Output turn-on delay time          | $t_{d(on)}$  | $V_{IN} = 3.6\text{ V}$ , $R_{LOAD} = 10\text{ }\Omega$ , $T_A = 25\text{ }^{\circ}\text{C}$                                                                                                    | -                                                          | 1.8               | -                 | ms            |
| Output turn-on rise time           | $t_{(on)}$   |                                                                                                                                                                                                 | 1.2                                                        | 2.5               | 3.8               |               |
| Output turn-off delay time         | $t_{d(off)}$ |                                                                                                                                                                                                 | -                                                          | -                 | 0.001             |               |

**Notes**

- a. The algebraic convention whereby the most negative value is a minimum and the most positive a maximum  
b. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing  
c. For  $V_{IN}$  outside this range consult typical EN threshold curve  
d. Not tested, guarantee by design


**PIN CONFIGURATION**


Top View

**Fig. 2 - TSOT23-6 Package**


| PIN DESCRIPTION |      |                                     |
|-----------------|------|-------------------------------------|
| PIN NUMBER      | NAME | FUNCTION                            |
| 1, 2            | OUT  | These are output pins of the switch |
| 3               | EN   | Enable input                        |
| 4               | GND  | Ground connection                   |
| 5, 6            | IN   | These are input pins of the switch  |

## BLOCK DIAGRAM




**Fig. 3 - Functional Block Diagram**


## TYPICAL CHARACTERISTICS (internally regulated, 25 °C, unless otherwise noted)




**Fig. 4 - Quiescent Current vs. Input Voltage**




**Fig. 6 - Quiescent Current vs. Temperature**




**Fig. 5 - Off Supply Current vs. Input Voltage**



**Fig. 7 - Off Supply Current vs. Temperature**



**Fig. 8 - Off Switch Current vs. Input Voltage**



**Fig. 9 -  $R_{DS(on)}$  vs.  $V_{IN}$**



**TYPICAL CHARACTERISTICS** (internally regulated, 25 °C, unless otherwise noted)




Fig. 10 - Output Pulldown vs. V<sub>IN</sub>




Fig. 13 - Output Pulldown vs. Temperature




Fig. 11 - Off Switch Current vs. Temperature




Fig. 14 - Reverse Blocking Current vs. Output Voltage




Fig. 12 - R<sub>DS(on)</sub> vs. Temperature











Fig. 15 - Rise Time vs. Temperature

**TYPICAL CHARACTERISTICS** (internally regulated, 25 °C, unless otherwise noted)

**Fig. 16 - Turn-On Delay Time vs. Temperature**

**Fig. 17 - Turn-Off Delay Time vs. Temperature**

**Fig. 18 - EN Threshold Voltage vs. Input Voltage**
**TYPICAL WAVEFORMS**

**Fig. 19 - Typical Turn-On Delay, Rise Time**  
 $C_{OUT} = 0.1 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $I_{OUT} = 1.5 A$ 

**Fig. 20 - Typical Fall Time**  
 $C_{OUT} = 0.1 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $I_{OUT} = 1.5 A$




2 V/Div, 0.25 A/Div, 2 ms/Div

**Fig. 21 - Typical Turn-On Delay, Rise Time**  
 $C_{OUT} = 0.1 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $R_{OUT} = 10 \Omega$




2 V/Div, 0.25 A/Div, 2  $\mu s$ /Div

**Fig. 24 - Typical Fall Time**  
 $C_{OUT} = 0.1 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $R_{OUT} = 10 \Omega$




2 V/Div, 2 A/Div, 2 ms/Div

**Fig. 22 - Typical Turn-On Delay, Rise Time**  
 $C_{OUT} = 200 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $I_{OUT} = 1.5 A$




2 V/Div, 2 A/Div, 2 ms/Div

**Fig. 25 - Typical Fall Time**  
 $C_{OUT} = 200 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $I_{OUT} = 1.5 A$



2 V/Div, 0.25 A/Div, 2 ms/Div

**Fig. 23 - Typical Turn-On Delay, Rise Time**  
 $C_{OUT} = 200 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $R_{OUT} = 10 \Omega$



2 V/Div, 0.25 A/Div, 2 ms/Div

**Fig. 26 - Typical Fall Time**  
 $C_{OUT} = 200 \mu F$ ,  $C_{IN} = 4.7 \mu F$ ,  $R_{OUT} = 10 \Omega$



## DETAILED DESCRIPTION

SiP32508 and SiP32509 are advanced slew rate controlled high side load switches consisted of a n-channel power switches. When a device is enable the gate of the power switch is turned on at a controlled rate to avoid excessive in-rush current. Once fully on the gate to source voltage of the power switch is biased at a constant level. The design gives a flat on resistance throughout the operating voltages. When the device is off, the reverse blocking circuitry prevents current from flowing back to input if output is raised higher than input. The reverse blocking mechanism also works in case of no input applied.

## APPLICATION INFORMATION

### Input Capacitor

SiP32508 and SiP32509 do not require input capacitor. To limit the voltage drop on the input supply caused by transient inrush currents, a input bypass capacitor is recommended. A 2.2  $\mu\text{F}$  ceramic capacitor placed as close to the  $V_{\text{IN}}$  and GND should be enough. Higher values capacitor can help to further reduce the voltage drop. Ceramic capacitors are recommended for their ability to withstand input current surge from low impedance sources such as batteries in portable devices.

### Output Capacitor

While these devices work without an output capacitor, an 0.1  $\mu\text{F}$  or larger capacitor across  $V_{\text{OUT}}$  and GND is recommended to accommodate load transient condition. It also helps preventing parasitic inductance from forcing  $V_{\text{OUT}}$  below GND when switching off. Output capacitor has minimal affect on device's turn on slew rate time. There is no requirement on capacitor type and its ESR.

### Enable

The EN pin is compatible with both TTL and CMOS logic voltage levels. Enable pin voltage can be above  $V_{\text{IN}}$  once it is within the absolute maximum rating range.

### Protection Against Reverse Voltage Condition

Both SiP32508 and SiP32509 contain reverse blocking circuitry to protect the current from going to the input from the output in case where the output voltage is higher than the input voltage when the main switch is off. Reverse blocking works for input voltage as low as 0 V.

### Thermal Considerations

SiP32508 and SiP32509 are designed to maintain a constant output load current. Due to physical limitations of the layout and assembly of the device the maximum switch current is 3 A, as stated in the Absolute Maximum Ratings table. However, another limiting characteristic for the safe operating load current is the thermal power dissipation of the package. To obtain the highest power dissipation (and a thermal resistance of 150  $^{\circ}\text{C}/\text{W}$ ) the in and out pins of the device should be connected to heat sinks on the printed circuit board. Figure 27 shows a demo board layout. All copper traces and vias for the in and out pins should be sized adequately to carry the maximum continuous current.

The maximum power dissipation in any application is dependent on the maximum junction temperature,  $T_{\text{J}}(\text{max.}) = 125^{\circ}\text{C}$ , the junction-to-ambient thermal resistance for the TSOT23-6 package,  $\theta_{\text{JA}} = 150^{\circ}\text{C}/\text{W}$ , and the ambient temperature,  $T_{\text{A}}$ , which may be formulaically expressed as:

$$P(\text{max.}) = \frac{T_{\text{J}(\text{max.})} - T_{\text{A}}}{\theta_{\text{JA}}} = \frac{125 - T_{\text{A}}}{150}$$

It then follows that, assuming an ambient temperature of 70  $^{\circ}\text{C}$ , the maximum power dissipation will be limited to about 367 mW.

So long as the load current is below the 3 A limit, the maximum continuous switch current becomes a function of two things: the package power dissipation and the  $R_{\text{DS(on)}}$  at the ambient temperature.

As an example let us calculate the worst case maximum load current at  $T_{\text{A}} = 70^{\circ}\text{C}$ . The worst case  $R_{\text{DS(on)}}$  at 25  $^{\circ}\text{C}$  occurs at an input voltage of 1.2 V and is equal to 55 m $\Omega$ . The  $R_{\text{DS(on)}}$  at 70  $^{\circ}\text{C}$  can be extrapolated from this data using the following formula:

$$R_{\text{DS(on)}}(\text{at } 70^{\circ}\text{C}) = R_{\text{DS(on)}}(\text{at } 25^{\circ}\text{C}) \times (1 + T_{\text{C}} \times \text{DT})$$


Where  $T_{\text{C}}$  is 3570 ppm/ $^{\circ}\text{C}$ . Continuing with the calculation we have

$$R_{\text{DS(on)}}(\text{at } 70^{\circ}\text{C}) = 52 \text{ m}\Omega \times (1 + 0.00357 \times (70^{\circ}\text{C} - 25^{\circ}\text{C})) = 60 \text{ m}\Omega$$

The maximum current limit is then determined by

$$I_{\text{LOAD(max.)}} < \sqrt{\frac{P(\text{max.})}{R_{\text{DS(on)}}}}$$

which in this case is 2.4 A. Under the stated input voltage condition, if the 2.4 A current limit is exceeded the internal die temperature will rise and eventually, possibly damage the device.




### Active EN Pull Down for Reverse Blocking

When an internal circuit detects the condition of  $V_{\text{OUT}}$  0.8 V higher than  $V_{\text{IN}}$ , it will turn on the pull down circuit connected to EN, forcing the switching off. The pull down value is about 1 k $\Omega$ .

## Pulse Current Capability

The device is mounted on the evaluation board shown in the PCB layout section. It is loaded with pulses of 5 A and 1 ms for periods of 4.6 ms.



The SiP32508 and SiP32509 can safely support 5 A pulse current repetitively at 25 °C.

## Switch Non-Repetitive Pulsed Current

The SiP32508 and SiP32509 can withstand inrush current of up to 12 A for 100  $\mu$ s at 25 °C when heavy capacitive loads are connected and the part is already enabled.

## Recommended Board Layout

For the best performance, all traces should be as short as possible to minimize the inductance and parasitic effects.

The input and output capacitors should be kept as close as possible to the input and output pins respectively.

Using wide traces for input, output, and GND to reducing the case to ambient thermal impedance.





Fig. 27 - Demo Board Layout

**PRODUCT SUMMARY**

| Part number                                        | SiP32508                                                                      | SiP32509                                                                                        |
|----------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Description                                        | 1.1 V to 5.5 V, 44 m $\Omega$ , 2.5 ms rise time, bidirectional off isolation | 1.1 V to 5.5 V, 44 m $\Omega$ , 2.5 ms rise time, bidirectional off isolation, output discharge |
| Configuration                                      | Single                                                                        | Single                                                                                          |
| Slew rate time ( $\mu$ s)                          | 2500                                                                          | 2500                                                                                            |
| On delay time ( $\mu$ s)                           | 1800                                                                          | 1800                                                                                            |
| Input voltage min. (V)                             | 1.1                                                                           | 1.1                                                                                             |
| Input voltage max. (V)                             | 5.5                                                                           | 5.5                                                                                             |
| On-resistance at input voltage min. (m $\Omega$ )  | 47                                                                            | 47                                                                                              |
| On-resistance at input voltage max. (m $\Omega$ )  | 44                                                                            | 44                                                                                              |
| Quiescent current at input voltage min. ( $\mu$ A) | 10.5                                                                          | 10.5                                                                                            |
| Quiescent current at input voltage max. ( $\mu$ A) | 105                                                                           | 105                                                                                             |
| Output discharge (yes / no)                        | No                                                                            | Yes                                                                                             |
| Reverse blocking (yes / no)                        | Yes                                                                           | Yes                                                                                             |
| Continuous current (A)                             | 3                                                                             | 3                                                                                               |
| Package type                                       | TSOT23-6                                                                      | TSOT23-6                                                                                        |
| Package size (W, L, H) (mm)                        | 3.0 x 2.9 x 1.0                                                               | 3.0 x 2.9 x 1.0                                                                                 |
| Status code                                        | 2                                                                             | 2                                                                                               |
| Product type                                       | Slew rate                                                                     | Slew rate                                                                                       |
| Applications                                       | Computers, consumer, industrial, healthcare, networking, portable             | Computers, consumer, industrial, healthcare, networking, portable                               |

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?62754](http://www.vishay.com/ppg?62754).

## Thin SOT-23 : 5- and 6-Lead (Power IC only)



- Notes:
1. Use millimeters as the primary measurement.
  2. Dimensioning and tolerances conform to ASME Y14.5M. - 1994.
  3. This part is fully compliant with JEDEC MO-193.
-  Detail of Pin #1 indentifier is optional.

| DIM.       | MILLIMETERS |      |      | INCHES     |       |       |
|------------|-------------|------|------|------------|-------|-------|
|            | MIN.        | NOM. | MAX. | MIN.       | NOM.  | MAX.  |
| A          | 0.91        | 1.00 | 1.10 | 0.036      | 0.039 | 0.043 |
| A1         | 0.00        | 0.05 | 0.10 | 0.000      | 0.002 | 0.004 |
| A2         | 0.85        | 0.90 | 1.00 | 0.033      | 0.035 | 0.039 |
| b          | 0.30        | 0.40 | 0.45 | 0.012      | 0.016 | 0.018 |
| c          | 0.10        | 0.15 | 0.20 | 0.004      | 0.006 | 0.008 |
| D          | 2.85        | 2.95 | 3.10 | 0.112      | 0.116 | 0.122 |
| E          | 2.70        | 2.85 | 2.98 | 0.106      | 0.112 | 0.117 |
| E1         | 1.525       | 1.65 | 1.70 | 0.060      | 0.065 | 0.067 |
| e          | 0.95 BSC    |      |      | 0.0374 BSC |       |       |
| L          | 0.30        | 0.40 | 0.50 | 0.014      | -     | 0.020 |
| L1         | 0.60 ref.   |      |      | 0.024 BSC  |       |       |
| L2         | 0.25 BSC    |      |      | 0.010 BSC  |       |       |
| $\theta$   | 0°          | 4°   | 8°   | 0°         | 4°    | 8°    |
| $\theta 1$ | 4°          | 10°  | 12°  | 4°         | 10°   | 12°   |

ECN: E13-1126-Rev. B, 01-Jul-13  
DWG: 5926



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.