


FRED Pt® **Ultrafast Soft Recovery Diode Module, 280 A**


HALF-PAK (D-67)


FEATURES

- 175 °C T_J operation
- Very low Q_{rr} and t_{rr}
- Designed and qualified for industrial level
- UL approved file E222165 
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

BENEFITS

- Reduced RFI and EMI
- Reduced snubbing
- Higher frequency operation

DESCRIPTION / APPLICATIONS

FRED Pt® diodes are optimized to reduce losses and EMI/RFI in high frequency power conditioning systems. The softness of the recovery eliminates the need for a snubber in most applications. These devices are ideally suited for HF welding, power converters, and other applications where switching losses are significant portion of the total losses.

PRIMARY CHARACTERISTICS

I _{F(AV)}	280 A
V _R	200 V
Q _{rr} (typical)	249 nC
t _{rr}	87 ns
Type	Modules - diode, FRED Pt®
Package	HALF-PAK (D-67)
Circuit configuration	Single

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Cathode to anode voltage	V _R		200	V
Continuous forward current	I _{F(DC)}	T _C = 25 °C	640	A
		T _C = 100 °C	400	
		T _C = 130 °C	280	
Maximum average forward current	I _{F(AV)}	T _J = 25 °C	1150	W
Single pulse forward current	I _{FSM}	T _C = 25 °C	789	
Maximum power dissipation	P _D	T _C = 100 °C	394	
Operating junction and storage temperature range	T _J , T _{Stg}		-55 to +175	°C

ELECTRICAL SPECIFICATIONS (T_J = 25 °C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Cathode to anode breakdown voltage	V _{BR}	I _R = 100 µA	200	-	-	V
Maximum forward voltage	V _{FM}	I _F = 200 A	-	0.94	1.0	
		I _F = 400 A	-	1.06	1.14	
		I _F = 200 A, T _J = 125 °C	-	0.8	-	
		I _F = 400 A, T _J = 125 °C	-	0.94	-	
Maximum reverse leakage current	I _{RM}	T _J = 175 °C, V _R = 200 V	-	0.67	1.5	mA
Series inductance	L _S	From top of terminal hole to mounting plane	-	7.0	-	nH

**DYNAMIC RECOVERY CHARACTERISTICS** ($T_J = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Reverse recovery time	t_{rr}	$T_J = 25\text{ }^{\circ}\text{C}$	-	87	-	ns
		$T_J = 125\text{ }^{\circ}\text{C}$	-	95	-	
Peak recovery current	I_{RRM}	$T_J = 25\text{ }^{\circ}\text{C}$	-	6	-	A
		$T_J = 125\text{ }^{\circ}\text{C}$	-	10.62	-	
Reverse recovery charge	Q_{rr}	$T_J = 25\text{ }^{\circ}\text{C}$	-	249	-	nC
		$T_J = 125\text{ }^{\circ}\text{C}$	-	493	-	

THERMAL - MECHANICAL SPECIFICATIONS

PARAMETER		SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum junction and storage temperature range		T _J , T _{Stg}		-55 to +175	°C
Maximum thermal resistance, junction to case		R _{thJC}	DC operation	0.19	°C/W
Typical thermal resistance, case to heatsink		R _{thCS}	Mounting surface, flat, smooth and greased	0.05	
Approximate weight				30	g
				1.06	oz.
Mounting torque	minimum			3 (26.5)	N · m (lbf · in)
	maximum			4 (35.4)	
Terminal torque	minimum			3.4 (30)	
	maximum			5 (44.2)	
Case style				HALF-PAK(D-67)	




Fig. 1 - Typical Forward Voltage Drop vs. Instantaneous Forward Current




Fig. 2 - Typical Reverse Current vs. Reverse Voltage









Fig. 3 - Maximum Current Rating Capability


Fig. 6 - Typical Reverse Recovery Time vs. di_F/dt

Fig. 4 - Typical Reverse Recovery vs. di_F/dt

Fig. 7 - Typical Reverse Recovery Charge vs. di_F/dt

Fig. 5 - Typical Recovery Current vs. di_F/dt

Fig. 8 - Typical Reverse Recovery Current vs. di_F/dt




Fig. 9 - Maximum Thermal Impedance Z_{thJC} Characteristics




Fig. 10 - Reverse Recovery Parameter Test Circuit




Fig. 11 - Reverse Recovery Waveform and Definitions




Fig. 12 - Avalanche Test Circuit and Waveforms

ORDERING INFORMATION TABLE


Device code	VS-VS	UD	200	C	H	20	PbF
	1	2	3	4	5	6	7

- 1 - Vishay Semiconductors product
- 2 - Ultrafast diode
- 3 - Current rating
- 4 - Circuit configuration:
C = Not isolated
- 5 - Type of device:
H = HALF-PAK (D-67)
- 6 - Voltage rating (20 = 200 V)
- 7 - Lead (Pb)-free

Circuit Configuration		
Circuit	Circuit Configuration Code	Circuit Drawing
Single diode	C	

LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95020

DIMENSIONS in millimeters (inches) **D-67 HALF-PAK**





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.